



■ ■ ■ Analysis Servers for FoxVigi

The Foxstream range of video analysis servers is an optimized hardware solution to use the FoxVigi software suite.

■ ■ ■ Key points

➤ Ready to use

To facilitate the deployment of video analysis solutions, the servers are delivered with a preinstalled version of FoxVigi software and integrate the components suitable for their operation (hard disk for alarm storage and input / output card).

➤ Performance & Reliability

The industrial components (motherboard, power supply and video surveillance hard drive) are selected and sized to ensure optimal management of video analysis.

The servers, guaranteed for 3 years, are designed and assembled in our premises in France.

➤ Flexibility

A complete range to adapt to all needs in video analysis solution:

- 8, 16 and 32 video channels for the analysis
- Compact or 3U rack-mountable format
- Inputs / outputs according to demand (8,16 and 32)

➤ Service Premium

The paid Premium Service Offer guarantees servers during 5 years. It also offers an Early Exchange service (shipment of equivalent equipment within 24 hours after diagnosis by the Foxstream support team)..

Technical Description

Product List

REFERENCES						
Without I/O	M-SER-8-C	M-SER-8-R	M-SER-16-C	M-SER-16-R	M-SER-32-C	M-SER-32-R
With I/O	M-SER-8-C-IO	M-SER-8-R-IO	M-SER-16-C-IO	M-SER-16-R-IO	M-SER-32-C-IO	M-SER-32-R-IO
# OF CHANNELS	8		16		32	
Format	COMPACT	RACK	COMPACT	RACK	COMPACT	RACK
CPU	CPU Mark > 3 500		CPU Mark > 4 300		CPU Mark > 8 600	
RAM	4 Go		4 Go		8 Go	
Network Interface	2 ports Gigabit Ethernet					
SSD (operating system)	256 Go					
HDD (alarm storage)	1 To		1 To		2 To	
Supply	300 W industrial type					
Fan	Industrial Type					
Operating System	Windows® 10 IoT Enterprise 2019 LTSC (ESD)					
USB Ports	2 front, 4 rear					
Video Outputs	VGA + DP + HDMI					
Dimensions	L 330 mm H 140 mm D 365 mm	3U Rack L 430mm H 134 mm D 400 mm	L 330 mm H 140 mm D 365 mm	3U Rack L 430mm H 134 mm D 400 mm	L 330 mm H 140 mm D 365 mm	3U Rack L 430mm H 134 mm D 400 mm
Weight	8 kg	13 kg	8 kg	13 kg	8 kg	13 kg
Conditions of use	Operating temperature: 0°C to 60°C Storage temperature: -20°C to 80°C Relative humidity: 5~95%, non-condensing					
Accessories	Keyboard + Mouse (without screen)					
GUARANTEE/SERVICE						
Standard	3 years					
Premium Service	Paid offer, 5 year guarantee + early exchange service (shipment of equivalent equipment within 24 hours after diagnosis by the Foxstream support team)					



Compact



Rack